



## CURVA SENZA SALDATURA

**R=2,5 D**


ASME B16.9

**R=2.5 D**

**SEAMLESS ELBOWS**

ASME B16.9

CARBON STEEL



D.E. Pollici Inches	Ø Est. Mm X Spess. Mm Outs. Diam. Mm X Thickn Mm	SCH	Raggio Radius	H	Peso Teorico Theoretical Weight Kg
1"	33,4 x 3,38	Std	72,5	89	0,28
	33,4 x 4,55	Xs			0,37
1 1/4"	42,4 x 3,56	Std	92,5	114	0,50
	42,4 x 4,85	Xs			0,65
1 1/2"	48,3 x 3,68	Std	107,5	132	0,68
	48,3 x 5,08	Xs			0,91
2"	60,3 x 3,91	Std	135	165	1,15
	60,3 x 5,54	Xs			1,59
3"	88,9 x 3,96	20	205	250	2,67
	88,9 x 5,49	Std			3,64
	88,9 x 7,62	Xs			4,92
3 1/2"	101,6 x 5,74	Std	237	288	5,05
	101,6 x 8,08	Xs			6,94
4"	114,3 x 4,37	20	270	327	5,02
	114,3 x 6,02	Std			6,82
	114,3 x 8,56	Xs			9,47
6"	168,3 x 4,76	20	390	474	11,81
	168,3 x 7,11	Std			17,31
	168,3 x 10,97	Xs			26,07
8"	219,1 x 6,35	20	510	619	26,69
	219,1 x 7,04	30			29,49
	219,1 x 8,18	Std			34,09
	219,1 x 10,31	60			42,53
	219,1 x 12,70	Xs			51,79

D.E. Pollici Inches	Ø Est. Mm X Spess. Mm Outs. Diam. Mm X Thickn Mm	SCH	Raggio Radius	H	Peso Teorico Theoretical Weight Kg
10"	273,0 x 6,35	20	650	786	42,64
	273,0 x 7,80	30			52,09
	273,0 x 9,27	Std			61,56
	273,0 x 12,70	Xs			83,24
12"	323,9 x 6,35	20	775	937	60,54
	323,9 x 8,38	30			79,38
	323,9 x 9,53	Std			89,94
	323,9 x 10,31	40			97,06
14"	323,9 x 12,70	Xs	850	1028	118,65
	355,6 x 6,35	10			73,02
	355,6 x 7,92	20			90,67
	355,6 x 9,53	Std			108,60
16"	355,6 x 11,13	40	406	610	126,24
	355,6 x 12,70	Xs			143,39
	406,4 x 6,35	10			95,46
	406,4 x 7,92	20			118,59
16"	406,4 x 9,53	Std	406	610	142,12
	406,4 x 12,70	Xs			187,88