



DERIVAZIONE FILETTATA

3000 - 6000 LBS

THREADED OUTLET

3000 - 6000 LBS

Diam. nominale Nominal pipe size	3000 - 6000					
	K ⁽¹⁾		M ⁽¹⁾		N ⁽¹⁾	
	mm	inches	mm	inches	mm	inches
1/4"	30.5	1.20	28.0	1.10	14.0	0.55
3/8"	30.5	1.20	32.0	1.26	17.4	0.69
1/2"	33.5	1.32	38.0	1.50	21.6	0.85
3/4"	35.0	1.38	44.5	1.75	26.9	1.06
1"	43.0	1.69	57.5	2.26	33.6	1.32
1 1/4"	48.0	1.89	63.5	2.50	42.4	1.67
1 1/2"	51.0	2.00	76.1	3.00	48.5	1.91
2"	57.5	2.26	92.0	3.62	60.9	2.40

⁽¹⁾ Le dimensioni non elencate nell'ANSI B 16.11-1980 e BS 3799-1974 possono variare a seconda del produttore.
Dimensions not listed in ANSI B 16.11-1980 and BS 3799-1974 may vary according to the manufacturer.

DA 1/4" A 2" O = 9,5 mm
 FROM 1/4" TO 2" O = 0,375 inch

Filettatura conforme a ANSI B 1.20.1 – Thread according to ANSI B 1.20.1