



NIPPLI RIDOTTI

ANSI B16.11
3000 - 6000 LBS

REDUCING HEXAGONAL NIPPLES

ANSI B16.11
3000 - 6000 LBS

Diam. nominale Nominal pipe size		A (mini)		E (mini)		F (mini)		C (mini)		W (mini)		b*			
inches	mm	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	3000		6000	
												mm	inches	mm	inches
1/4" x 1/8"	8 x 6	15	0.59	15	0.59	10	0.39	6	0.24	31	1.22	5	0.20	2	0.08
3/8" x 1/4"	10 x 8	18	0.71	16	0.63	15	0.59	8	0.31	39	1.54	8	0.31	6	0.24
1/2" x 3/8"	15 x 10	22	0.87	20	0.79	16	0.63	8	0.31	44	1.73	11	0.43	8	0.31
1/2" x 1/4"	15 x 8	22	0.87	20	0.79	15	0.59	8	0.31	43	1.69	8	0.31	6	0.24
3/4" x 1/2"	20 x 15	27	1.06	21	0.83	20	0.79	9	0.35	50	1.97	14	0.55	11	0.43
3/4" x 3/8"	20 x 10	27	1.06	21	0.83	16	0.63	9	0.35	46	1.81	11	0.43	8	0.31
1" x 3/4"	25 x 20	35	1.38	25	0.98	21	0.83	10	0.39	56	2.20	19	0.75	13	0.51
1" x 1/2"	25 x 15	35	1.38	25	0.98	20	0.79	10	0.39	55	2.17	14	0.55	11	0.43
1 1/2" x 1"	40 x 25	50	1.97	26	1.02	25	0.98	16	0.63	67	2.64	24	0.94	17	0.67
1 1/2" x 3/4"	40 x 20	50	1.97	26	1.02	21	0.83	16	0.63	63	2.48	19	0.75	13	0.51
1 1/2" x 1/2"	40 x 15	50	1.97	26	1.02	20	0.79	16	0.63	62	2.44	14	0.55	11	0.43
2" x 1 1/2"	50 x 40	62	2.44	27	1.06	26	1.02	17	0.67	70	2.76	38	1.50	30	1.18
2" x 1"	50 x 25	62	2.44	27	1.06	25	0.98	18	0.71	70	2.76	24	0.94	17	0.67
2" x 3/4"	50 x 20	62	2.44	27	1.06	21	0.83	17	0.67	65	2.60	19	0.75	13	0.51
2" x 1/2"	50 x 15	62	2.44	27	1.06	20	0.79	18	0.71	65	2.60	14	0.55	11	0.43

(*) La dimensione «b» è nominale e soggetta alle normali tolleranze di fabbricazione.
Dimension «b» is nominal and is subject to normal MANUFACTURE tolerances.

Filettatura conforme a ANSI B 1.20.1 – Thread according to ANSI B 1.20.1