



MANICOTTO RIDOTTO

ANSI B16.11
3000 - 6000 LBS

REDUCING COUPLING

ANSI B16.11
3000 - 6000 LBS

Diam. nominale Nominal pipe size	3000				6000			
	W ⁽¹⁾		D ⁽¹⁾		W ⁽¹⁾		D ⁽¹⁾	
	mm	inches	mm	inches	mm	inches	mm	inches
3/8" x 1/4"	38.10	1.50	22.35	0.88	38.10	1.50	31.75	1.25
1/2" x 3/8"	47.75	1.88	28.45	1.12	47.75	1.88	38.10	1.50
1/2" x 1/4"	47.75	1.88	28.45	1.12	47.75	1.88	38.10	1.50
3/4" x 1/2"	50.80	2.00	35.05	1.38	50.80	2.00	44.45	1.75
3/4" x 1/4"	50.80	2.00	35.05	1.38	50.80	2.00	44.45	1.75
1" x 3/4"	60.45	2.38	44.45	1.75	60.45	2.38	57.15	2.25
1" x 1/2"	60.45	2.38	44.45	1.75	60.45	2.38	57.15	2.25
1" x 1/4"	60.45	2.38	44.45	1.75	60.45	2.38	57.15	2.25
1 1/4" x 1"	66.55	2.62	57.15	2.25	66.55	2.62	63.50	2.50
1 1/2" x 1"	79.25	3.12	63.50	2.50	79.25	3.12	76.20	3.00
1 1/2" x 3/4"	79.25	3.12	63.50	2.50	79.25	3.12	76.20	3.00
1 1/2" x 1/2"	79.25	3.12	63.50	2.50	79.25	3.12	76.20	3.00
2" x 1 1/2"	85.85	3.38	76.20	3.00	85.85	3.38	91.95	3.62
2" x 1"	85.85	3.38	76.20	3.00	85.85	3.38	91.95	3.62
2 1/2" x 2"	91.95	3.62	91.95	3.62	90.95	3.62	107.95	4.25
3" x 2"	107.95	4.25	107.95	4.25	107.95	4.25	127.00	5.00
4" x 3"	120.65	4.75	139.70	5.50	120.65	4.75	158.75	6.25
4" x 2"	120.65	4.75	139.70	5.50	120.65	4.75	158.75	6.25

⁽¹⁾ Le dimensioni non elencate nell'ANSI B 16.11-1980 e BS 3799-1974 possono variare a seconda del produttore.
Dimensions not listed in ANSI B 16.11-1980 and BS 3799-1974 may vary according to the manufacturer.