



MANICOTTI S.W.

ANSI B 16.11
3000 - 6000 LBS

COUPLINGS S.W.

ANSI B 16.11
3000 - 6000 LBS

Diam. nominale Nominal pipe size	Coste di montaggio / Laying lengths											
	Manicotti / Couplings - E						Mezzi manicotti / Half couplings - F					
	3000		6000		Tolleranze ± Tolerances ±		3000		6000		Tolleranze ± Tolerances ±	
	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches
1/4"	6.5	0.25	6.5	0.25	1.5	0.06	16.0	0.62	16.0	0.62	1.0	0.03
3/8"	6.5	0.25	6.5	0.25	3.0	0.12	17.5	0.69	17.5	0.69	1.5	0.06
1/2"	9.5	0.38	9.5	0.38	3.5	0.12	22.5	0.88	22.5	0.88	1.5	0.06
3/4"	9.5	0.38	9.5	0.38	3.5	0.12	23.5	0.94	23.5	0.94	1.5	0.06
1"	13.0	0.50	13.0	0.50	4.0	0.16	29.0	1.12	29.0	1.12	2.0	0.08
1 1/4"	13.0	0.50	13.0	0.50	4.0	0.16	30.0	1.19	30.0	1.19	2.0	0.08
1 1/2"	13.0	0.50	13.0	0.50	4.0	0.16	32.0	1.25	32.0	1.25	2.0	0.08
2"	19.0	0.75	19.0	0.75	4.0	0.16	41.0	1.62	41.0	1.62	2.0	0.08
2 1/2"	19.0	0.75	19.0	0.75	5.0	0.20	42.5	1.69	42.5	1.69	2.5	0.10
3"	19.0	0.75	19.0	0.75	5.0	0.20	44.5	1.75	44.5	1.75	2.5	0.10
4"	19.0	0.75	19.0	0.75	5.0	0.20	47.5	1.88	47.5	1.88	2.5	0.10