



### GOMITI

ANSI B 16.11  
3000 - 6000 LBS

### ELBOWS

ANSI B 16.11  
3000 - 6000 LBS

Diam. nominale Nominal pipe size	Dal centro alla base del raccordo A Center to bottom of socket A										
	90°					45°				Tolleranze ± Tolerances ±	
	3000		6000		3000		6000				
	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	
1/4"	11.0	0.44	13.5	0.53	8.0	0.31	8.0	0.31	1.0	0.03	
3/8"	13.5	0.53	15.5	0.62	7.5	0.31	11.5	0.44	1.5	0.06	
1/2"	15.5	0.62	19.5	0.75	11.5	0.44	12.5	0.50	1.5	0.06	
3/4"	19.5	0.75	22.5	0.88	12.5	0.50	14.5	0.56	1.5	0.06	
1"	22.0	0.88	27.0	1.06	14.0	0.56	17.0	0.69	2.0	0.08	
1 1/4"	27.0	1.06	32.0	1.25	17.0	0.69	21.0	0.81	2.0	0.08	
1 1/2"	32.0	1.25	38.0	1.50	21.0	0.81	25.0	1.00	2.0	0.08	
2"	38.0	1.50	41.0	1.62	25.0	1.00	29.0	1.12	2.0	0.08	
2 1/2"	41.5	1.62			29.0	1.12			2.5	0.10	
3"	57.5	2.25			31.5	1.25			2.5	0.10	
4"	66.5	2.62			41.5	1.62			2.5	0.10	

- Per quote B - C - D - G - J si vedano caratteristiche dimensionali a pag. 134
- For dimensions B - C - D - G - J refer to dimensions of s.w. fittings shown in page 134