



STUB-ENDS SHORT LENGTH

ASME B16.9 ASTM A 403
WP 304/304L E WP 316/316L

CARATTERISTICHE TECNICHE

Ricavati da tubo senza saldatura o saldato.
Norme dimensionali e tolleranze: ASME B16.9/B16.25
MARCATURA: in accordo ASTM/ASME B16.9 e MSS SP-25
CERTIFICATI EN 10204/3.1

STUB-ENDS SHORT LENGTH

ASME B16.9 ASTM A 403
WP 304/304L AND WP 316/316L

TECHNICAL INFORMATION

Made from seamless or welded pipe.
Dimensional standard and tolerances: ASME B16.9/B16.25
MARKING: according to ASTM/ASME B16.9 and MSS SP-25
CERTIFICATES EN 10204/3.1

Ø est. mm x Spess. mm Outs. diam. mm x Thckn mm	Dimensioni Dimensions	Peso Kg/pz. Weight Kg/pcs.	F	G	R
21.34 x 2.11	1/2" SCH 10S	0.07	50.8	34.9	3.18
21.34 x 2.77	1/2" SCH 40S	0.09	50.8	34.9	3.18
26.67 x 2.11	3/4" SCH 10S	0.10	50.8	42.9	3.18
26.67 x 2.87	3/4" SCH 40S	0.12	50.8	42.9	3.18
33.40 x 2.77	1" SCH 10S	0.16	50.8	50.8	3.18
33.40 x 3.38	1" SCH 40S	0.17	50.8	50.8	3.18
42.16 x 2.77	1.1/4" SCH 10S	0.22	50.8	63.5	4.76
42.16 x 3.56	1.1/4" SCH 40S	0.25	50.8	63.5	4.76
48.26 x 2.77	1.1/2" SCH 10S	0.25	50.8	73.0	6.35
48.26 x 3.68	1.1/2" SCH 40S	0.31	50.8	73.0	6.35
60.33 x 2.77	2" SCH 10S	0.43	63.5	92.1	7.94
60.33 x 3.91	2" SCH 40S	0.61	63.5	92.1	7.94
73.03 x 3.05	2.1/2" SCH 10S	0.57	63.5	104.8	7.94
73.03 x 5.16	2.1/2" SCH 40S	0.80	63.5	104.8	7.94
88.90 x 3.05	3" SCH 10S	0.73	63.5	127.0	9.53
88.90 x 5.49	3" SCH 40S	1.13	63.5	127.0	9.53
114.30 x 3.05	4" SCH 10S	1.09	76.2	157.2	11.11
114.30 x 6.02	4" SCH 40S	1.87	76.2	157.2	11.11
141.30 x 3.40	5" SCH 10S	1.47	76.2	185.7	11.11
141.30 x 6.55	5" SCH 40S	2.28	76.2	185.7	11.11
168.28 x 3.40	6" SCH 10S	2.15	88.9	215.9	12.70
168.28 x 7.11	6" SCH 40S	3.57	88.9	215.9	12.70
219.08 x 3.76	8" SCH 10S	3.22	101.6	269.9	12.70
219.08 x 8.18	8" SCH 40S	6.07	101.6	269.9	12.70
273.05 x 4.19	10" SCH 10S	5.13	127.0	323.9	12.70
273.05 x 9.27	10" SCH 40S	10.07	127.0	323.9	12.70
323.85 x 4.57	12" SCH 10S	8.16	152.4	381.0	12.70
323.85 x 9.53	12" SCH 40S	14.29	152.4	381.0	12.70
355.60 x 4.78	14" SCH 10S	10.89	152.4	412.8	12.70
406.40 x 4.78	16" SCH 10S	12.70	152.4	469.9	12.70
457.20 x 4.78	18" SCH 10S	17.24	152.4	533.4	12.70
508.00 x 5.54	20" SCH 10S	21.77	152.4	584.2	12.70