



### TAPPO FEMMINA

ANSI B16.11  
3000 - 6000 LBS

### CAPS

ANSI B16.11  
3000 - 6000 LBS

Diam. nominale Nominal pipe size	3000						6000					
	P		D		G		P		D		G	
	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches
1/4"	25	1.00	19	0.75	5.0	0.19	27	1.06	25	1.00	6.5	0.25
3/8"	25	1.00	22	0.88	5.0	0.19	27	1.06	32	1.25	6.5	0.25
1/2"	32	1.25	29	1.12	6.5	0.25	33	1.31	38	1.50	8.0	0.31
3/4"	37	1.44	35	1.38	6.5	0.25	38	1.50	44	1.75	8.0	0.31
1"	41	1.62	44	1.75	9.5	0.38	43	1.69	57	2.25	11.0	0.44
1 1/4"	44	1.75	57	2.25	9.5	0.38	46	1.81	64	2.50	11.0	0.44
1 1/2"	44	1.75	64	2.50	11.0	0.44	48	1.88	76	3.00	12.5	0.50
2"	48	1.88	76	3.00	12.5	0.50	51	2.00	92	3.62	16.0	0.62
2 1/2"	60	2.38	92	3.62	16.0	0.62	64	2.50	108	4.25	19.0	0.75
3"	65	2.56	108	4.25	19.0	0.75	68	2.69	127	5.00	22.0	0.88
4"	68	2.69	140	5.50	22.0	0.88	75	2.94	159	6.25	28.5	1.12

Filettatura conforme a ANSI B 1.20.1 – Thread according to ANSI B 1.20.1