



GOMITI 45°
ANSI B16.11
3000 - 6000 LBS

45° ELBOWS
ANSI B16.11
3000 - 6000 LBS

Diam. nominale Nominal pipe size	3000						6000					
	C		H		G		C		H		G	
	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches
1/4"	19	0.75	25	1.00	3.5	0.130	22	0.88	33	1.31	6.5	0.260
3/8"	22	0.88	33	1.31	3.5	0.138	25	1.00	38	1.50	7.0	0.275
1/2"	25	1.00	38	1.50	4.0	0.161	29	1.12	46	1.81	8.0	0.321
3/4"	29	1.12	46	1.81	4.5	0.170	33	1.31	56	2.19	8.5	0.336
1"	33	1.31	56	2.19	5.0	0.196	35	1.38	62	2.44	10.0	0.391
1 1/4"	35	1.38	62	2.44	5.5	0.208	43	1.69	75	2.97	10.5	0.417
1 1/2"	43	1.69	75	2.97	5.5	0.219	44	1.72	84	3.31	11.0	0.436
2"	45	1.72	84	3.31	7.0	0.281	52	2.06	102	4.00	12.0	0.476
2 1/2"	52	2.06	102	4.00	7.5	0.301	64	2.50	121	4.75	15.5	0.602
3"	64	2.50	121	4.75	9.0	0.348	79	3.12	146	5.75	16.5	0.655
4"	79	3.12	152	6.00	11.00	0.440	79	3.12	152	6.00	18.5	0.735

Filettatura conforme a ANSI B 1.20.1 – Thread according to ANSI B 1.20.1