



CARATTERISTICHE TECNICHE:

Esecuzione: microfusione
 Dimensioni: ISO 4144 e tipo EN 10241 (EX DIN 2986)
 Filettatura: conforme a EN 10226-1 (EX ISO 7-1)
 Acciaio: AISI 316/EN 1.4401, AISI 316L/EN 1.4404, AISI 304/EN 1.4301, AISI 304L/EN 1.4407
 Pressione d'esercizio: 150 Lbs-PN10
Certificati EN 10204/2.1

TECHNICAL INFORMATION:

Execution: microcasting
 Dimensional standard ISO 4144 and type EN 10241 (EX DIN 2986)
 Thread: according to EN 10226-1 (EX ISO 7-1)
 Steel: AISI 316/EN 1.4401, AISI 316L/EN 1.4404, AISI 304/EN 1.4301, AISI 304L/EN 1.4407
 Rate pressure: 150 Lbs-PN10
Certificates EN 10204/2.1

**IF 270 MANICOTTO
 COUPLING**

ISO 4144

**IFE 270 MANICOTTO
 IFE 274 MANICOTTO
 COUPLING**

EN-10241

Tipo Standard Standard Type	Size mm	1/8"	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
ISO 4144	Ø 1	13	16,5	20	24,5	30	37,5	46,5	53	65,5	82	95,5	121,5
	L	17	24	25	32	35	41	45	45	54	63	69	81
	SP/THK	1,5	1,5	1,5	1,6	1,7	1,9	2,2	2,4	2,7	3,2	3,6	4,1
Tipo Pesante Heavy Type	Size mm	1/8"	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
EN-10241	Ø 1	15	18,5	21,3	26,6	31,8	39,5	48,3	54,5	66,2	82	95	121
	L	17	25	26	34	36	43	48	48	56	65	71	83
	SP/THK	2,0/2,6	2.3/2.9	2.3/2.9	2.6/3.2	3.2/4.0	3.2/4.0	3.2/4.0	3.2/4.0	3.6/4.5	3.6/4.5	4.0/5.0	4,5/5,4

//= NON FORNIBILE / NOT SUPPLIED