



TEES UGUALI E RIDOTTI SBOCCATI

CARATTERISTICHE TECNICHE

I raccordi a T sono ricavati da tubo saldato o lamiera

Dimensioni e tolleranze tipo EN 10253-3

Marcatura: in accordo EN 10253-3

CERTIFICATI EN 10204/2.2

EQUAL AND REDUCER PULLED TEES

TECHNICAL INFORMATION

Tee are made out of welded pipe or plate

Dimensions and tolerances type EN 10253-3

Marking: according to EN 10253-3

CERTIFICATES EN 10204/2.2

Diam. nominale Nominal diam.			Diam. esterno Outs. diam.			Spessore / Thickness	
DNØ	DN mm	DN ₁	D ₁ mm	F mm	h mm	2,00 mm	3,00 mm
50	60,3	50	60,3	50	3	☒	☒
		40	48,3		3	❖	❖
		32	42,4		2	❖	❖
		25	33,7		2	❖	❖
65	76,1	65	76,1	65	4	☒	☒
		50	60,3		3	❖	❖
		40	48,3		3	❖	❖
		32	42,4		2	❖	❖
80	88,9	80	88,9	80	5	☒	☒
		65	76,1		4	❖	❖
		50	60,3		3	❖	❖
		40	48,3		3	❖	❖
100	114,3	100	114,3	100	7	☒	☒
		80	88,9		5	❖	❖
		65	76,1		4	❖	❖
		50	60,3		3	❖	❖
125	139,7	125	139,7	125	8	☒	☒
		100	114,3		7	❖	❖
		80	88,9		5	❖	❖
		65	76,1		4	❖	❖

Diam. nominale Nominal diam.			Diam. esterno Outs. diam.			Spessore / Thickness	
DNØ	DN mm	DN ₁	D ₁ mm	F mm	h mm	2,00 mm	3,00 mm
150	168,3	150	168,3	150	10	☒	☒
		125	139,7		8	❖	❖
		100	114,3		7	❖	❖
		80	88,9		5	❖	❖
200	219,1	200	219,1	200	12	☒	☒
		150	168,3		10	❖	❖
		125	139,7		8	❖	❖
		100	114,3		7	❖	❖
250	273	250	273	250	13	☒	☒
		200	219,1		12	❖	❖
		150	168,3		10	❖	❖
		125	139,7		8	❖	❖

☒ = Disponibile a magazzino

❖ = Disponibile a richiesta

// = Non fornibile

On stock

On request

Not supplied